

NO.	Series	Size	SL/XL	Sidewall Type	Rim	PR	LI/SS	Max. Load Capacity (KG)	Max. Load Capacity (LBS)	Max.Air Pressure (KPa)	Max.Air Pressure (PSI)	Tread Depth (mm)	Section Width (mm)	Overall Diameter (mm)
1	60"	195/60R16C	-	BSW	6.0	8	99/97T	775/730	1709/1609	375	54	8	201	640
2	65"	205/65R16C	-	BSW	6.0	8	107/105R	975/925	2149/2039	475	69	8	209	672
3		215/65R16C	-	BSW	6.5	8	109/107R	1030/975	2271/2149	475	69	8	221	686
4		225/65R16C	-	BSW	6.5	8	112/110R	1120/1060	2469/2337	475	69	8	228	698
5		235/65R16C	-	BSW	7.0	8	115/113R	1215/1150	2679/2535	475	69	8	240	712
6	70"	195/70R15C	-	BSW	6.0	8	104/102R	900/850	1984/1874	450	65	8	201	655
7		215/70R15C	-	BSW	6.5	8	109/107R	1030/975	2271/2149	450	65	8	221	683
8		225/70R15C	-	BSW	6.5	8	112/110R	1120/1060	2469/2337	450	65	8	228	697
9	75"	195/75R16C	-	BSW	5.5	8	107/105R	975/925	2149/2039	475	69	8	196	698
10		205/75R16C	-	BSW	5.5	8	110/108R	1060/1000	2337/2205	475	69	8	203	714
11		215/75R16C	-	BSW	6.0	8	113/111R	1150/1090	2535/2403	475	69	8	216	728